

# Want to learn or work without distractions? Our AE-39 USB headset is your answer.

This headset includes thoughtful touches like an all-ages, fully adjustable headband and a widely compatible USB connector to make this headset your go-to for remote classrooms and conferences.

- Mid-sized earpads can provide a good balance between coverage and fit, accommodating a wider range of head and ear sizes.
- A lightweight design can be more comfortable for extended listening sessions, as they can reduce the pressure and fatigue that can come with heavier headphone
- Ideal for testing and assessments in school, work, and home environments
- USB connection provides a more reliable, responsive and quality audio experience







#### **VOLUME CONTROL**

Inline volume control to easily increase, decrease or mute the volume.

# **BOOM MICROPHONE**

Noise-canceling microphone minimizes surrounding noise to properly capture even the quietest of speakers.

## **EXTRA COMFORT**

Soft padded headband and earpads provide hours of comfort.

### **OUR AUDIO SOLUTIONS ARE:**

- · Durable and reliable
- · Easy to store and clean
- Meets safety compliances
- Compatible across many platforms and devices



In-line volume controls



Noise-canceling mic and adjustable boom arm



Chew resistant nylonbraided cord and strain relief at earcups



Available with USB-A connection



## **AE-39 HEADSET**

Item number

USB-A

Black: 2AE39GRYUSB32

Audio

Driver size: 40 mm

Magnet material: Ferrite

Impedance: 32 ohms

Sensitivity: 108 dB +/- 3 dB @ 1 kHz

w 1mW input

Frequency response: 20 Hz - 20 kHz

Voice

Mic style: Boom,120 degree rotation
Mic type: Noise-canceling, Bidirectional

Mic sensitivity: -38 dB V/Pa +/- 3dB

General

Plug type: USB-A

Cord material: Nylon braided

Cord length: 6 feet

Ear pads: PU Leatherette Earcup type: On-ear, Fixed

Headband: Padded, adjustable

50

Weight: 131 grams

Package: Polybag

Compliances: CA Prop 65, CPSIA, TSCA, SOR 2014, RoHS, TSCA, REACH SVHC, REACH Annex XVII, POPS SCCPs & HBCDD, SPL EN 50332-2, ICES-003, CE-EMC, FCC-SDOC

Packing: